




## 製品仕様

<b>Size</b>	6RU
<b>4K</b>	6ch (2SI/SQD) 12G-SDI, 3G-SDI Level A, 10bit HDR
<b>HD</b>	4ch, 6ch, 8ch, 12ch +
<b>VoIP</b>	SMPTE 2022, 2110, NMOS on 10Gbp SFP+
<b>Storage</b>	4K : 30h~ 60h HD : 180h~360h SAS HDD 1.8TB × 6 or 12
<b>EVS Network</b>	Xnet-VIA over 10Gbps IP Xnet [2] 3Gbps SDTI
<b>Media Network</b>	10GbE SFP+ /1GbE
<b>High Frame Rate</b>	4K : 2x, 3x 倍速対応 HD : 2x, 3x, 4x, 6x, 8x, 10x, 16x 倍速対応
<b>Codec</b>	4K : XAVC4K class 300, 480, DNxHR HD : AVC-Intra, XAVC HD, ProRes, DNxHD Proxy : MJPEG, H.264
<b>Multi Viewer</b>	2 × SDI-IN / 4 × SDI-OUT
<b>Audio</b>	エンベデット, MADI, AES/EBU, アナログモニタリング
<b>Protocol</b>	LSM remote, VDCP, Odetics, Sony BVW75, XtenDD35, EVS AVSP/IPDP, Linx
<b>Controller</b>	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p><b>LSM remote</b></p>  </div> <div style="text-align: center;"> <p>ライブグラフィックス <b>Epsio Paint/FX</b></p>  </div> <div style="text-align: center;"> <p>4K 切り出しシステム <b>Epsio Zoom</b></p>  </div> </div>

